



**Parklex®**

**HY TEK**

**New floors: woods and textures**

**March 2017**


**New woods that combine their own virtues, natural touch and warmth, with the technical requirements for good flooring installation both in residential spaces and in high traffic surfaces.**



Parklex is a company that specialises in wood for architecture. At our facilities, we manufacture different natural wood boards, processing them to eliminate the need for any form of maintenance or further treatment. Architects, interior designers, companies and individual consumers have already installed our products worldwide. This experience makes us knowledgeable of the key factors for innovation.



Hy Tek is a high-density composite wood flooring for interiors, suitable for high traffic areas such as hotels, offices, museums, airports and shops.







Wood: Rustic Oak

Slats with different widths can be combined (2 or 3 widths). Assembly with narrow slats of 107 mm implies that all slats are produced with bevelled edge.

For installation and assembly we recommend following the detailed instructions in the Hy Tek technical guide or simply contact the Parklex technical department.

**Four different slat widths allow to install Hy Tek flooring in the same way that it was mounted traditionally, in which different widths and lengths were mixed.**

The moisture resistant surface treatment, applicable to all surface finishes and woods, allows the installation of Hy Tek flooring in areas with frequent contact with water.



Wood: Olivier Ash



Wood: Smoked Grey Oak

Matte

With lesser light refraction than a glossy finish, it presents a smooth and easily cleaned surface. Recommended for high-traffic public spaces.

Ultramatte

The least light refracting finish. Its smooth surface allows the intrinsic characteristics of wood to stand out. Recommended for spaces that require anti-slip surfaces. Achieved the best result (Class 2) in the slip resistance tests in accordance with the Spanish CTE code.

Texture

The pressure exerted on the wood during the production process allows a slight texture to be generated on the surface of the wood, produced by its grain and figure.

Ultramatte Texture

A textured finish with minimum light refraction. Recommended for spaces that require anti-slip surfaces. Achieved the best result (Class 2) in the slip resistance tests in accordance with the Spanish CTE code.





Wood: Olivier Ash

**Polígono Alkaiaga, c/ Baldrún  
31780 Bera - Navarra - Spain  
Tel. +34 948 625 045  
parklex@parklex.com**

**www.parklex.com**